SHOWERDEC®

Create a user friendly wetroom quickly & simply.

SHOWERDEC® FEATURES

- Creates a complete level access wetroom shower area concealed beneath the vinyl or tiled flooring once installed.
- Exceptionally strong design FEA* tested to withstand weights of **297KG / 46 Stone** with minimal deflection.
- 24mm thick for strength and rigidity.
- 40mm flat area around the floor former perimeter for shower doors to sit securely onto.
- Larger shower area, ideal for wheelchairs.
- Extensive range of practical half height shower doors available, see pages 42 47.
- Supplied **without** waste. 2 part, 50mm water seal gravity trap available, see opposite.
- Lifetime guarantee.

*Finite Element Analysis (FEA) is a computerised method for predicting how a product reacts & behaves to real world physical forces.

INSTALLER FRIENDLY

- No raised collar around the underside of the waste making installation on timber floors easier.
- Circular ribbed underside designed for setting into a concrete or screed base and eliminates slippage when installing.
- Textured top surface allows excellent adhesion of vinyl flooring.
- Excellent falls built into the top surface.
- Pre-formed semi-drilled fixing points.
- Can be cut to size in virtually any position using a circular saw or jigsaw.
- Suitable for timber & screeded floors.
- Offset waste positions to avoid joists.



ShowerDec® details on your phone or tablet.










CONLOUR











Reference	Tray Size		Reference	Tray Size	
	A	В		A	В
SD900x900	900	900	SD1500x820	1500	820
SD1000x1000	1000	1000	SD1500x1000	1500	1000
SD1200x750	1200	750	SD1500x1200	1500	1200
SD1200x1200	1200	1200	SD1800x820	1800	820
SD1300x800	1300	800	SD1800x900	1800	900
SD1400x900	1400	900			

ShowerDecs® are not handed.

-	Suits wooden floors	7	Choice of gravity wastes available
	Suits screeded floors	6.16	CUW01 pumped waste available
LEVEL ACCESS	No height difference from the floor when installed	TI	1800x820mm & 1800x900mm: Cut to size bath replacement

Waste options

ShowerDec floor formers are **NOT** supplied with a waste gully, but we have a range available to suit most adaptations:



CTW01

2 part, 50mm water seal trapped waste.



TSG52

Round stainless steel option for flexible sheet flooring.



VSG₁

Non return valve gully for shallow floor depths.



150mm stainless steel option for use with floor tiles.


See pages 81 & 83 for full details for all gravity & pumped waste options.




SHOWERDEC®


ShowerDec® floor former options illustrated below. Use the shower door selector located on the inside front cover fold-out page to assist with your door selection.

SHOWERDEC® 900x900






SHOWERDEC® 1000x1000








Reference Code floor former illustrated SD900x900


ShowerDec 1000x1000 Reference Code floor former illustrated SD1000x1000

ShowerDec 1200x750 Reference Code floor former illustrated SD1200x750


SHOWERDEC® 1200x1200







SHOWERDEC® 1400x900




ShowerDec 1200x1200 Reference Code floor former illustrated SD1200x1200 above, not handed




ShowerDec 1400x900 Reference Code floor former illustrated SD1400x900 above, not handed


SHOWERDEC® 1500x820



SHOWERDEC® 1500x1000



SHOWERDEC® 1500x1200



floor former illustrated





ShowerDec 1500x820 Reference Code floor former illustrated SD1500x820

SHOWERDEC® 1800x820

SHOWERDEC® 1800x900

floor former illustrated





SD1500x1000

To view door option images see pages 42 - 47 or use the inside front cover fold-out page.

ShowerDec 1800x820 Reference Code floor former illustrated SD1800x820 above, not handed

ShowerDec 1800x900 Reference Code floor former illustrated SD1800x900 above, not handed